

LHS 410 SF-R



To the product



Technical data

Article	170.913; 170.914; 170.915; 170.916; 170.917; 170.918; 170.919	
Phases	1x	
Voltage	120-400 V	
Current	5-19.5 A	
Power	2000-5500 W	
Max. air outlet temperature	650 °C	1202 °F
Min. airflow	160-420 l/min	5.65-14.83 cfm
Max. air inlet temperature	350 °C	662 °F
Max. ambient temperature	65 °C	149 °F
Overheating protection	No	
Max. inlet pressure	100 kPa	14.5 psi
Nozzle connection ø	50 mm / 2 in	
Display	No	
Length	178 mm	7 in
Width	81 mm	3.18 in
Height	293 mm	11.53 in
Weight	1.89 kg	4.16 lb
Approvals	CE; S+; cURus	
Protection class	I	



LHS 410 SF-R

Product items

170.913	LHS 410 SF-R, 120V/2kW
170.914	LHS 410 SF-R, 230V/2kW
170.915	LHS 410 SF-R, 230V/3.6kW
170.916	LHS 410 SF-R, 230V/4.4kW
170.917	LHS 410 SF-R, 400V/2kW
170.918	LHS 410 SF-R, 400V/4.4kW
170.919	LHS 410 SF-R, 400V/5.5kW