

LHS 61S CLASSIC



To the product

Technical data

Phases	1x; 3x	
Voltage	230-480 V	
Current	5-21 A	
Power	4000-9000 W	
Max. air outlet temperature	650 °C	1202 °F
Min. airflow	310-690 l/min	10.94-24.36 cfm
Max. air inlet temperature	65 °C	149 °F
Max. ambient temperature	65 °C	149 °F
Overheating protection	No	
Alarm output	Normally open contact	
Max. inlet pressure	100 kPa	14.5 psi
Nozzle connection ø	62 mm / 2.45 in	
Display	No	
Length	363.0 mm	14.29 in
Width	116.0 mm	4.56 in
Height	136.0 mm	5.35 in
Weight	3.15 kg	6.94 lb
Approvals	CE; S+; UKCA	
Protection class	I	



LHS 61S CLASSIC

Product items

143.490	LHS 61S CLASSIC, 3 x 400V/6kW
143.696	LHS 61S CLASSIC, 3 x 230V/6kW
143.697	LHS 61S CLASSIC, 3 x 400V/9kW
143.698	LHS 61S CLASSIC, 3 x 480V/6kW
143.707	LHS 61S CLASSIC, 3 x 230V/4kW
143.708	LHS 61S CLASSIC, 3 x 400V/4kW
143.709	LHS 61S CLASSIC, 3 x 480V/4kW
145.730	LHS 61S CLASSIC, 480V/8kW
145.732	LHS 61S CLASSIC, 400V/8.5kW