

MISTRAL 6 PREMIUM



关于产品



技术数据

相位	1x	
电压	120–230 V	
电流	10–20 A	
功率	2300–4500 W	
频率	50/60 Hz; 60 Hz	
最高出风温度	430–650 °C	806–1202 °F
风量 (20°C)	300–400 l/min	10.59–14.12 cfm
最高进气温度	60 °C	140 °F
最高环境温度	65 °C	149 °F
过热保护	有	
静风压	2500–3000 Pa	0.36–0.43 psi
风嘴接口ø	36.5 mm / 1.45 in; 50 mm / 2 in	
噪声等级	65 dB (A)	
显示	无	
长度	321.2–352.2 mm	12.64–13.86 in
宽度	90 mm	3.54 in
高度	91.2 mm	3.59 in
重量	1.3–1.5 kg	2.86–3.3 lb
认证	CE; EAC; KC; S+; UKCA; cURus	
保护等级	II	



MISTRAL 6 PREMIUM

订货号

146.522	MISTRAL 6 PREMIUM, 220V/3100W, ø50mm, 60Hz, KC
147.965	MISTRAL 6 PREMIUM, 120V/2400W, ø50mm
147.966	MISTRAL 6 PREMIUM, 230V/3400W, ø50mm
147.967	MISTRAL 6 PREMIUM, 230V/4500W, ø50mm
148.006	MISTRAL 6 PREMIUM, 230V/2300W, ø36.5mm