

MISTRAL 6 PREMIUM



To the product

Technical data

Phases	1x	
Voltage	120-230 V	
Current	10-20 A	
Power	2300-4500 W	
Frequency	50/60 Hz; 60 Hz	
Max. air outlet temperature	430-650 °C	806-1202 °F
Airflow (20°C)	300-400 l/min	10.59-14.12 cfm
Max. air inlet temperature	60 °C	140 °F
Max. ambient temperature	65 °C	149 °F
Overheating protection	Yes	
Static pressure	2500-3000 Pa	0.36-0.43 psi
Nozzle connection ø	36.5 mm / 1.45 in; 50 mm / 2 in	
Noise emission level	65 dB (A)	
Display	No	
Length	321.2-352.2 mm	12.64-13.86 in
Width	90 mm	3.54 in
Height	91.2 mm	3.59 in
Weight	1.3-1.5 kg	2.86-3.3 lb
Approvals	CE; EAC; KC; S+; UKCA; cURus	
Protection class	II	



MISTRAL 6 PREMIUM

Product items

146.522	MISTRAL 6 PREMIUM, 220V/3100W, ø50mm, 60Hz, KC
147.965	MISTRAL 6 PREMIUM, 120V/2400W, ø50mm
147.966	MISTRAL 6 PREMIUM, 230V/3400W, ø50mm
147.967	MISTRAL 6 PREMIUM, 230V/4500W, ø50mm
148.006	MISTRAL 6 PREMIUM, 230V/2300W, ø36.5mm