

MISTRAL 6 SYSTEM



To the product

Technical data

Article	146.524; 146.701; 147.968; 147.969; 147.972; 147.973; 147.975	
Phases	1x	
Voltage	100-230 V	
Current	10-20 A	
Power	1500-4500 W	
Frequency	50/60 Hz; 60 Hz	
Air temperature control	Closed loop	
Max. air outlet temperature	650 °C	1202 °F
Airflow (20°C)	100-400 l/min	3.53-14.12 cfm
Max. air inlet temperature	60 °C	140 °F
Max. ambient temperature	65 °C	149 °F
Overheating protection	Yes	
Static pressure	3500 Pa	0.5 psi
Nozzle connection ø	36.5 mm / 1.45 in; 50 mm / 2 in	
Noise emission level	65 dB (A)	
Display	Yes	
Interfaces	0-10V; 4-20mA	
Length	321.2-352.2 mm	12.64-13.86 in
Width	90.0 mm	3.54 in
Height	91.2 mm	3.59 in



MISTRAL 6 SYSTEM

Technical data

Weight	1.2-1.5 kg	2.64-3.3 lb
Approvals	CE; KC; S+; UKCA; cURus	
Protection class	II	

Product items

146.524	MISTRAL 6 SYSTEM, 220V/3100W, 60Hz
146.701	MISTRAL 6 SYSTEM, 230V/3400W
147.968	MISTRAL 6 SYSTEM, 230V/4500W
147.969	MISTRAL 6 SYSTEM, 120V/2400W
147.972	MISTRAL 6 SYSTEM, 100V/1500W
147.973	MISTRAL 6 SYSTEM, 200V/3000W
147.975	MISTRAL 6 SYSTEM, 230V/2300W