

KRELUS G14-25 MINI-MINI



To the product



Technical data

Article	122.604; 122.609; 122.657; 122.785; 123.850; 123.852; 124.166; 124.217; 124.624; 124.629; 124.636; 124.672; 124.706	
Voltage	200-240 V	
Current	4.16-5.42 A	
Frequency	50/60 Hz	
Power	904-1300 W	
Power density	28.93-41.6 kW/m ²	18.66-26.83 W/in ²
Max. ambient temperature	500 °C	932 °F
Pyrometer hole position	Standard; Without	
Length	248 mm	9.76 in
Width	123 mm	4.84 in
Height	65 mm	2.55 in
Weight	1.35 kg	2.97 lb
Approvals	CE	
Protection class (IEC 60529)	IP20	
Protection class	I	

KRELUS G14-25 MINI-MINI

Product items

122.604	KRELUS IR-Heater G14-25 MM 3, 230V/1000W
122.609	KRELUS IR-Heater G14-25 MM 3.3, 230V/1200W
122.657	KRELUS IR-Heater G14-25 MM 3 PS, 230V/1000W
122.785	KRELUS IR-Heater G14-25 MM 3.3 PS, 230V/1200W
123.850	KRELUS IR-Heater G14-25 MM 3, 220V/915W
123.852	KRELUS IR-Heater G14-25 MM 3, 240V/1090W
124.166	KRELUS IR-Heater G14-25 MM 3 PS, 220V/915W
124.217	KRELUS IR-Heater G14-25 MM 3 PS, 240V/1090W
124.624	KRELUS IR-Heater G14-25 MM 3.3, 220V/1090W
124.629	KRELUS IR-Heater G14-25 MM 3.3, 240V/1300W
124.636	KRELUS IR-Heater G14-25 MM 3.3 PS, 200V/904W
124.672	KRELUS IR-Heater G14-25 MM 3.3 PS, 220V/1090W
124.706	KRELUS IR-Heater G14-25 MM 3.3 PS, 240V/1300W