

KRELUS G14-25 MINI-MINI



Vers le produit



Données techniques

Article	122.604; 122.609; 122.657; 122.785; 123.850; 123.852; 124.166; 124.217; 124.624; 124.629; 124.636; 124.672; 124.706	
Tension	200-240 V	
Courant	4.16-5.42 A	
Fréquence	50/60 Hz	
Performance	904-1300 W	
Densité de puissance	28.93-41.6 kW/m ²	18.66-26.83 W/in ²
Température ambiante max.	500 °C	932 °F
Position du trou du pyromètre	Sans; Standard	
Longueur	248 mm	9.76 in
Largeur	123 mm	4.84 in
Hauteur	65 mm	2.55 in
Poids	1.35 kg	2.97 lb
Agréments	CE	
Classe de protection (IEC 60529)	IP20	
Classe de protection	I	

KRELUS G14-25 MINI-MINI

Articles

122.604	KRELUS IR-Heater G14-25 MM 3, 230V/1000W
122.609	KRELUS IR-Heater G14-25 MM 3.3, 230V/1200W
122.657	KRELUS IR-Heater G14-25 MM 3 PS, 230V/1000W
122.785	KRELUS IR-Heater G14-25 MM 3.3 PS, 230V/1200W
123.850	KRELUS IR-Heater G14-25 MM 3, 220V/915W
123.852	KRELUS IR-Heater G14-25 MM 3, 240V/1090W
124.166	KRELUS IR-Heater G14-25 MM 3 PS, 220V/915W
124.217	KRELUS IR-Heater G14-25 MM 3 PS, 240V/1090W
124.624	KRELUS IR-Heater G14-25 MM 3.3, 220V/1090W
124.629	KRELUS IR-Heater G14-25 MM 3.3, 240V/1300W
124.636	KRELUS IR-Heater G14-25 MM 3.3 PS, 200V/904W
124.672	KRELUS IR-Heater G14-25 MM 3.3 PS, 220V/1090W
124.706	KRELUS IR-Heater G14-25 MM 3.3 PS, 240V/1300W