

KRELUS G14-25 MINI-MINI



Informazioni sul prodotto



Dati tecnici

Articolo	122.604; 122.609; 122.657; 122.785; 123.850; 123.852; 124.166; 124.217; 124.624; 124.629; 124.636; 124.672; 124.706	
Tensione	200-240 V	
Corrente	4.16-5.42 A	
Frequenza	50/60 Hz	
Prestazioni	904-1300 W	
Densità di potenza	28.93-41.6 kW/m ²	18.66-26.83 W/in ²
Max. temperatura ambiente	500 °C	932 °F
Posizione del foro del pirometro	Senza; Standard	
Lunghezza	248 mm	9.76 in
Larghezza	123 mm	4.84 in
Altezza	65 mm	2.55 in
Peso	1.35 kg	2.97 lb
Approvazioni	CE	
Classe di protezione (IEC 60529)	IP20	
Classe di protezione	I	

KRELUS G14-25 MINI-MINI

Articoli

122.604	KRELUS IR-Heater G14-25 MM 3, 230V/1000W
122.609	KRELUS IR-Heater G14-25 MM 3.3, 230V/1200W
122.657	KRELUS IR-Heater G14-25 MM 3 PS, 230V/1000W
122.785	KRELUS IR-Heater G14-25 MM 3.3 PS, 230V/1200W
123.850	KRELUS IR-Heater G14-25 MM 3, 220V/915W
123.852	KRELUS IR-Heater G14-25 MM 3, 240V/1090W
124.166	KRELUS IR-Heater G14-25 MM 3 PS, 220V/915W
124.217	KRELUS IR-Heater G14-25 MM 3 PS, 240V/1090W
124.624	KRELUS IR-Heater G14-25 MM 3.3, 220V/1090W
124.629	KRELUS IR-Heater G14-25 MM 3.3, 240V/1300W
124.636	KRELUS IR-Heater G14-25 MM 3.3 PS, 200V/904W
124.672	KRELUS IR-Heater G14-25 MM 3.3 PS, 220V/1090W
124.706	KRELUS IR-Heater G14-25 MM 3.3 PS, 240V/1300W