

KRELUS G14-25 MINI-MINI



Acerca del producto



Datos técnicos

Artículo	122.604; 122.609; 122.657; 122.785; 123.850; 123.852; 124.166; 124.217; 124.624; 124.629; 124.636; 124.672; 124.706	
Voltaje	200-240 V	
Corriente	4.16-5.42 A	
Frecuencia	50/60 Hz	
Potencia	904-1300 W	
Densidad de potencia	28.93-41.6 kW/m ²	18.66-26.83 W/in ²
Temperatura ambiente máx.	500 °C	932 °F
Posición del orificio del pirómetro	Estándar; Sin	
Longitud	248 mm	9.76 in
Ancho	123 mm	4.84 in
Altura	65 mm	2.55 in
Peso	1.35 kg	2.97 lb
Aprobaciones	CE	
Clase de protección (IEC 60529)	IP20	
Clase de protección	I	

KRELUS G14-25 MINI-MINI

Artículos

122.604	KRELUS IR-Heater G14-25 MM 3, 230V/1000W
122.609	KRELUS IR-Heater G14-25 MM 3.3, 230V/1200W
122.657	KRELUS IR-Heater G14-25 MM 3 PS, 230V/1000W
122.785	KRELUS IR-Heater G14-25 MM 3.3 PS, 230V/1200W
123.850	KRELUS IR-Heater G14-25 MM 3, 220V/915W
123.852	KRELUS IR-Heater G14-25 MM 3, 240V/1090W
124.166	KRELUS IR-Heater G14-25 MM 3 PS, 220V/915W
124.217	KRELUS IR-Heater G14-25 MM 3 PS, 240V/1090W
124.624	KRELUS IR-Heater G14-25 MM 3.3, 220V/1090W
124.629	KRELUS IR-Heater G14-25 MM 3.3, 240V/1300W
124.636	KRELUS IR-Heater G14-25 MM 3.3 PS, 200V/904W
124.672	KRELUS IR-Heater G14-25 MM 3.3 PS, 220V/1090W
124.706	KRELUS IR-Heater G14-25 MM 3.3 PS, 240V/1300W