

ASO



To the product



Technical data

Blower type	Radial blower	
Phases	1x; 3x	
Voltage at 50 Hz	230 V; 230/400 V	
Voltage at 60 Hz	265/460 V	
Frequency	50 Hz; 50/60 Hz	
Blower power at 50 Hz	550 W	
Blower power at 60 Hz	660 W	
Airflow (20 °C) at 50 Hz	12000 l/min	423.77 cfm
Airflow (20 °C) at 60 Hz	13800 l/min	487.33 cfm
Static pressure at 50 Hz	1450 Pa	0.21 psi
Static pressure at 60 Hz	2070 Pa	0.3 psi
Max. air inlet temperature	200 °C	392 °F
Max. ambient temperature	60 °C	140 °F
Noise emission level	70 dB (A)	
Air inlet (outer diameter)	134 mm	5.27 in
Air outlet (outer diameter)	90 mm	3.54 in
Length	366 mm	14.4 in
Width	361 mm	14.21 in
Height	366 mm	14.4 in
Weight	15 kg	33.06 lb
Power cable length	0-3 m	0-9.84 ft



ASO

Technical data

Plug	EU, 3 poles, 16A; without plug
Approvals	CE; EAC; UKCA
Protection class (IEC 60529)	IP54
Protection class	I

Product items

103.527	ASO, 3 x 230/400V 50Hz, 3 x 265/460V 60Hz
103.530	ASO, 1 x 230V/550W 50Hz, EU plug