

# SOLANO AT



**To the product**

## Technical data

Article	162.263; 162.265; 162.267; 162.269; 162.271; 162.273; 162.275; 162.277	
Voltage	100 V; 120 V; 220 V; 230 V	
Frequency	50/60 Hz; 60 Hz	
Power	1500-2300 W	
Temperature	50-650 °C	122-1202 °F
Temperature setting stepless	Yes	
Airflow (20°C)	210-350 l/min	7.41-12.36 cfm
Stepless air volume adjustment	Yes	
Static pressure	2300 Pa	0.33 psi
Eco-Mode	Yes	
Display	Yes	
e-Drive	No	
Outdoor use	No	
Nozzle connection ø	36.5 mm / 1.45 in	
Length	270 mm	10.62 in
Width	75 mm	2.95 in
Height	240 mm	9.44 in
Handle diameter	45 mm	1.77 in
Weight	0.75 kg	1.65 lb
Power cable length	3 m	9.84 ft



# SOLANO AT

## Technical data

Plug	AU, 3 poles, 10A; CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; JP, 2 poles, 15A; KR, 2 poles, 16A; UK, 3 poles, 13A; US, 2 poles, 15A, polarized
Noise emission level	< 65 dB(A)
Approvals	CE; KC; S+; UL
Protection class	II
Approval number	R-R-LE1-SolanoAT
Country of origin	Switzerland

## Product items

162.263	SOLANO AT, 230V/2300W, EU plug
162.265	SOLANO AT, 230V/2300W, CH plug
162.267	SOLANO AT, 230V/2300W, UK plug
162.269	SOLANO AT, 230V/2300W, AU plug
162.271	SOLANO AT, 220V/2100W, KR plug
162.273	SOLANO AT, 120V/1800W, US plug
162.275	SOLANO AT, 100V/1500W, JP plug
162.277	SOLANO AT, 230V/2300W, CN plug