TRIAC ST EASYFLOOR Kit

To the product

Technical data

Article	163.136; 163.243	
Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	1600 W	
Temperature	40–700 °C	104–1292 °F
Temperature setting stepless	Yes	
Airflow (20°C)	240 l/min	8.47 cfm
Stepless air volume adjustment	No	
Static pressure	3000 Pa	0.43 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in	
Length	338 mm	13.3 in
Device diameter	90 mm	3.54 in
Handle diameter	56 mm	2.2 in
Weight	0.99 kg	2.18 lb
Power cable length	3 m	9.84 ft
Plug	EU, 2 poles, 16A; US, 2 poles, 15A	
Noise emission level	67 dB (A)	

© Copyright Leister Technologies AG, 2026 | Subject to changes

TRIAC ST EASYFLOOR Kit

Technical data

Approvals	CE; UL
Protection class	II
Country of origin	Switzerland

Scope of delivery

Tubular nozzle (ø 31.5) ø 5 mm, 37 mm; Speed welding nozzle (ø 8.0) Profile D ø 5; EASYFLOOR; Cylinder brush, brass ø 5 mm; Heating Element; Tool case

Product items

163.136	TRIAC ST, 230V/1600W, EASYFLOOR Kit, EU plug
163.243	TRIAC ST, 120V/1600W, EASYFLOOR Kit, US plug

© Copyright Leister Technologies AG, 2026 | Subject to changes