

PENWELD A



关于产品



技术数据

订货号	173.367; 173.368; 173.369; 173.370; 173.371; 173.376; 173.377; 173.666; 175.598; 177.344; 177.346	
电压	120 V; 230 V	
频率	50/60 Hz	
功率	1000–1550 W	
温度	60–600 °C	140–1112 °F
无级温度调节	有	
空气软管长度	3–8 m	9.84–26.24 ft
显示	有	
户外应用	有	
风嘴接口ø	31.5 mm / 1.25 in; M14	
长度	254–282 mm	10–11.1 in
设备直径	54 mm	2.12 in
手柄直径	37 mm	1.45 in
重量	0.43–0.48 kg	0.94–1.05 lb
插头	CH T11, 2极, 10A ₀ ; CN, 2极, 10A; 欧盟, 2极, 16A; 美国, 2极, 15A	
认证	CB认证; CE	
保护等级	II	
原籍国	瑞士	

PENWELD A

订货号

173.367	PENWELD 305-A, 230V/1000W, 3m, M14, 欧标插头
173.368	PENWELD 305-A, 120V/1000W, 3m, M14, 美国插头
173.369	PENWELD 305-A, 230V/1000W, 3m, M14, 瑞标插头
173.370	PENWELD 305-A, 230V/1000W, 8m, M14, 欧标插头
173.371	PENWELD 305-A, 230V/1000W, 8m, M14, 瑞标插头
173.376	PENWELD 500-A, 230V/1550W, 3m, 欧标插头
173.377	PENWELD 500-A, 120V/1550W, 3m, 美国插头
173.666	PENWELD 305-A, 120V/1000W, 8m, M14, 美国插头
175.598	PENWELD 505-A, 230V/1550W, 8m, M14, 欧盟插头
177.344	PENWELD 500-A, 230V/1550W, 3m, 国标插头
177.346	PENWELD 505-A, 230V/1550W, 8m, M14, 国标插头