

PENWELD A



Over het product



Technische gegevens

Artikel	173.367; 173.368; 173.369; 173.370; 173.371; 173.376; 173.377; 173.666; 175.598; 177.344; 177.346	
Spanning	120 V; 230 V	
Frequentie	50/60 Hz	
Vermogen	1000-1550 W	
Temperatuur	60-600 °C	140-1112 °F
Temperatuurstelling traploos	Ja	
Lengte luchtslang	3-8 m	9.84-26.24 ft
Weergave	Ja	
Buitengebruik	Ja	
Aansluiting mondstuk ø	31.5 mm / 1.25 in; M14	
Lengte	254-282 mm	10-11.1 in
Diameter van het apparaat	54 mm	2.12 in
Diameter handvat	37 mm	1.45 in
Gewicht	0.43-0.48 kg	0.94-1.05 lb
Stekker	CH T11, 2-polig, 10A; CN, 2-polig, 10A; EU, 2-polig, 16A; US, 2-polig, 15A	
Goedkeuringen	CB Certificering; CE	
Beschermingsklasse	II	
Land van herkomst	Zwitserland	

PENWELD A

Artikel

173.367	PENWELD 305-A, 230V/1000W, 3m, M14, EU stekker
173.368	PENWELD 305-A, 120V/1000W, 3m, VS stekker
173.369	PENWELD 305-A, 230V/1000W, 3m, M14, CH stekker
173.370	PENWELD 305-A, 230V/1000W, 8m slang, EU stekker
173.371	PENWELD 305-A, 230V/1000W, 8m, M14, CH stekker
173.376	PENWELD 500-A, 230V/1550W, 3m, EU stekker
173.377	PENWELD 500-A, 120V/1550W, 3m, VS stekker
173.666	PENWELD 305-A, 120V/1000W, 8m, VS stekker
175.598	PENWELD 505-A, 230V/1550W, 8m, M14, EU stekker
177.344	PENWELD 500-A, 230V/1550W, 3m, CN stekker
177.346	PENWELD 505-A, 230V/1550W, 8m, M14, CN stekker