

# PENWELD A



**To the product**

## Technical data

Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	1000-1550 W	
Temperature	60-600 °C	140.0-1112.0 °F
Temperature setting stepless	Yes	
Display	Yes	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in; M14	
Length	254.0-282.0 mm	10.0-11.1 in
Device diameter	54 mm	2.12 in
Handle diameter	37 mm	1.45 in
Weight	0.43-0.48 kg	0.94-1.05 lb
Power cable length	0.5 m	1.64 ft
Approvals	CB Certification; CE; UKCA	
Protection class	II	
Country of origin	CH	



# PENWELD A

## Product items

---

173.367	PENWELD 305-A, 230V/1000W, 3m, M14, EU plug
173.368	PENWELD 305-A, 120V/1000W, 3m, M14, US plug
173.369	PENWELD 305-A, 230V/1000W, 3m, M14, CH plug
173.370	PENWELD 305-A, 230V/1000W, 8m, M14, EU plug
173.371	PENWELD 305-A, 230V/1000W, 8m, M14, CH plug
173.376	PENWELD 500-A, 230V/1550W, 3m, EU plug
173.377	PENWELD 500-A, 120V/1550W, 3m, US plug
175.598	PENWELD 505-A, 230V/1550W, 8m, M14, EU plug
177.344	PENWELD 500-A, 230V/1550W, 3m, CN plug
177.346	PENWELD 505-A, 230V/1550W, 8m, M14, CN plug