

PENWELD S



To the product

Technical data

Article	173.372; 173.373; 173.374; 173.375; 173.378; 173.379; 177.345; 179.377	
Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	1000-1550 W	
Temperature	60-600 °C	140-1112 °F
Temperature setting stepless	Yes	
Air hose length	1-8 m	3.28-26.24 ft
Display	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in; M14	
Length	254-275 mm	10-10.82 in
Device diameter	54 mm	2.12 in
Handle diameter	37 mm	1.45 in
Weight	0.41-0.46 kg	0.9-1.01 lb
Plug	CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; US, 2 poles, 15A	
Approvals	CE	
Protection class	II	
Country of origin	Switzerland	



PENWELD S

Product items

173.372	PENWELD 305-S, 230V/1000W, 3m, M14, EU plug
173.373	PENWELD 305-S, 230V/1000W, 3m, M14, CH plug
173.374	PENWELD 305-S, 120V/1000W, 3m, M14, US plug
173.375	PENWELD 305-S, 230V/1000W, 8m, M14, EU plug
173.378	PENWELD 500-S, 230V/1550W, 3m, EU plug
173.379	PENWELD 500-S, 120V/1550W, 3m, US plug
177.345	PENWELD 500-S, 230V/1550W, 3m, CN plug
179.377	PENWELD 500-S, 230V/1550W, 1m, EU plug