

# COMET 500

COMET 500, 230V/2300W, copper 60x50mm test channel, indoor-Set, CEE 3/16  
Article 170.561



**To the product item**

## Technical data

Article	170.561	
Frequency	50/60 Hz	
Power	2300 W	
Temperature	80-460 °C	176-860 °F
Speed	0.8-8 m/min	2.62-26.24 ft/min
Welding Technology	Hot wedge	
Hot wedge length	60 mm	2.36 in
Hot wedge width	50 mm	1.96 in
Hot wedge material	Copper	
Max. overlap	125 mm	4.92 in
Max. welding pressure	1000 N	224.8 lbf
Weld seam width	2 x 15 mm / 2 x 0.59 in	
Travel roller equipment	Indoor-Kit	
LQS	No	
Display	Yes	
Length	325 mm	12.79 in
Width	245 mm	9.64 in
Height	260 mm	10.23 in
Weight	9.2 kg	20.28 lb
Welding materials	FPO; HDPE; LDPE; LLDPE; PE; PP; TPO	
Weldable material thicknesses	0.5-3 mm	19.68-118.11 mil
Power cable length	3 m	9.84 ft
Plug	CEE blue, 3 poles, 16A	



# COMET 500

COMET 500, 230V/2300W, copper 60x50mm test channel, indoor-Set, CEE 3/16  
Article 170.561

## Technical data

---

Approvals	CE
Protection class	I
Country of origin	Switzerland

---

## Scope of delivery

---

151.847 Cylinder brush, brass  $\varnothing$  15 mm; 162.760 Tool case