

VARIANT T1



To the product



Technical data

Voltage	200 V; 230 V; 400 V	
Frequency	50/60 Hz	
Power	3680-5700 W	
Speed	1.5-18.0 m/min	4.92-59.05 ft/min
Temperature	100-620 °C	212.0-1148.0 °F
Air volume adjustable	Yes	
Welding nozzle / seam width	20-40 mm	0.78-1.57 in
LQS	No	
Brushless blower motor	Yes	
Brushless drive motor	No	
Length	700.0 mm	27.55 in
Width	400.0 mm	15.74 in
Height	230.0 mm	9.05 in
Weight	22.0 kg	48.5 lb
Power cable length	1.2 m	3.93 ft
Approvals	CE; UKCA	
Protection class	I	
Country of origin	CH	

Scope of delivery

Additional weight; Nozzle adjustment gauge; Handle long



VARIANT T1

Product items

141.891	VARIANT T1, 230V/3680W, 40mm, EU plug
141.892	VARIANT T1, 230V/3680W, 20mm, EU plug
141.893	VARIANT T1, 400V/5700W, 40mm, CEE 5/16
141.894	VARIANT T1, 400V/5700W, 20mm, CEE 5/16
147.739	VARIANT T1, 200V/4200W, 40mm, w/o plug
147.748	VARIANT T1, 200V/4200W, 20mm, w/o plug
156.145	VARIANT T1, 230V/3680W, 40mm, CEE 3/16