

VARIANT 700



Vers le produit



Données techniques

Article	176.859; 176.860; 176.861; 176.862; 176.863; 176.864; 176.865; 176.866; 176.867	
Tension	230 V; 400 V	
Fréquence	50/60 Hz	
Performance	3680-5500 W	
Vitesse	1-20 m/min	3.28-65.62 ft/min
Température	100-620 °C	212-1148 °F
Volume d'air réglable	Oui	
Buse de soudage / largeur de soudure	20-50 mm	0.78-1.96 in
LQS	Non	
Moteur de soufflerie sans balais	Oui	
Longueur	800 mm	31.49 in
Largeur	562 mm	22.12 in
Hauteur	347 mm	13.66 in
Poids	24.3 kg	53.57 lb
Fiche	CEE bleu, 3 pôles, 16A; CEE rouge, 5 pôles, 16A; UE, 3 pôles, 16A	
Agréments	CE	
Pays d'origine	Suisse	

VARIANT 700

Articles

176.859	VARIANT 700, 230V/3680W, 50mm, prise UE
176.860	VARIANT 700, 230V/3680W, 40mm, prise UE
176.861	VARIANT 700, 230V/3680W, 20mm, prise UE
176.862	VARIANT 700, 230V/3680W, 50mm, CEE 3/16
176.863	VARIANT 700, 230V/3680W, 40mm, CEE 3/16
176.864	VARIANT 700, 230V/3680W, 20mm, CEE 3/16
176.865	VARIANT 700, 400V/5500W, 50mm, CEE 5/16
176.866	VARIANT 700, 400V/5500W, 40mm, CEE 5/16
176.867	VARIANT 700, 400V/5500W, 20mm, CEE 5/16