

UNIPLAN 510



关于产品



技术数据

订货号	177.403; 177.404; 177.406; 179.071; 179.072; 179.073; 179.077; 179.078; 179.079; 179.086; 179.087; 179.088; 179.090	
电压	120 V; 230 V	
频率	50/60 Hz	
功率	1800–3450 W	
速度	1–16 m/min	3.28–52.49 ft/min
温度	100–620 °C	212–1148 °F
风量可调	有	
风嘴/焊缝宽度	20–30 mm	0.78–1.18 in
焊接质量监控 (LQS)	无	
无刷鼓风机电机	有	
长度	500 mm	19.68 in
宽度	310 mm	12.2 in
高度	300 mm	11.81 in
重量	16 kg	35.27 lb
插头	CEE蓝色, 3极, 16A.; CN, 3极, 16A; 无插头; 欧盟, 3极, 16A; 美国, 3极, 15A	
电源线长度	3 m	9.84 ft
认证	CB认证; CE	
保护等级	I	
原籍国	瑞士	



UNIPLAN 510

交付范围

折边和穿绳导向件; 材料抬升装置; 配重支架底座; 短手柄; 手柄支架; 风嘴调整规; 钢丝刷; 2× 配重块; 工具箱

订货号

177.403	UNIPLAN 510, 230V/3450W, 40mm, CN 16(2P+PE)
177.404	UNIPLAN 510, 230V/3450W, 30mm, CN 16(2P+PE)
177.406	UNIPLAN 510, 230V/3450W, 20mm, CN 16(2P+PE)
179.071	UNIPLAN 510, 120V/1800W, 20mm, 美标插头
179.072	UNIPLAN 510, 120V/1800W, 30mm, 美标插头
179.073	UNIPLAN 510, 120V/1800W, 40mm, 美标插头
179.077	UNIPLAN 510, 230V/3450W, 20mm, CEE 3/16A UK
179.078	UNIPLAN 510, 230V/3450W, 30mm, CEE 3/16A UK
179.079	UNIPLAN 510, 230V/3450W, 40mm, CEE 3/16A UK
179.086	UNIPLAN 510, 230V/3450W, 40mm, 欧标插头
179.087	UNIPLAN 510, 230V/3450W, 30mm, 欧标插头
179.088	UNIPLAN 510, 230V/3450W, 20mm, 欧标插头
179.090	UNIPLAN 510, 230V/3450W, 40mm, 无插头