

UNIPLAN 310



关于产品



技术数据

订货号	177.401; 177.402; 179.074; 179.075; 179.080; 179.081; 179.082; 179.083; 179.084; 179.085; 179.089	
电压	120 V; 230 V	
频率	50/60 Hz	
功率	1800–3450 W	
速度	1–16 m/min	3.28–52.49 ft/min
温度	100–620 °C	212–1148 °F
风量可调	有	
风嘴/焊缝宽度	40 mm	1.57 in
焊接质量监控 (LQS)	无	
无刷鼓风机电机	无	
长度	500 mm	19.68 in
宽度	310 mm	12.2 in
高度	300 mm	11.81 in
重量	15 kg	33.06 lb
插头	CEE蓝色, 3极, 16A; CN, 3极, 16A; 无插头; 欧盟, 3极, 16A; 美国, 3极, 15A	
电源线长度	3 m	9.84 ft
认证	CB认证; CE	
保护等级	I	
原籍国	瑞士	



UNIPLAN 310

交付范围

工具箱

订货号

177.401	UNIPLAN 310, 230V/3450W, 40mm, CN 16(2P+PE)
177.402	UNIPLAN 310, 230V/3450W, 30mm, CN 16(2P+PE)
179.074	UNIPLAN 310, 120V/1800W, 30mm, 美标插头
179.075	UNIPLAN 310, 120V/1800W, 40mm, 美标插头
179.080	UNIPLAN 310, 230V/3450W, 20mm, CEE 3/16
179.081	UNIPLAN 310, 230V/3450W, 30mm, CEE 3/16
179.082	UNIPLAN 310, 230V/3450W, 40mm, CEE 3/16
179.083	UNIPLAN 310, 230V/3450W, 40mm, 欧标插头
179.084	UNIPLAN 310, 230V/3450W, 30mm, 欧标插头
179.085	UNIPLAN 310, 230V/3450W, 20mm, 欧标插头
179.089	UNIPLAN 310, 230V/3450W, 40mm, 无插头