

UNIPLAN 310



Zum Produkt



Technische Daten

Artikel	177.401; 177.402; 179.074; 179.075; 179.080; 179.081; 179.082; 179.083; 179.084; 179.085; 179.089	
Spannung	120 V; 230 V	
Frequenz	50/60 Hz	
Leistung	1800-3450 W	
Geschwindigkeit	1-16 m/min	3.28-52.49 ft/min
Temperatur	100-620 °C	212-1148 °F
Luftmenge einstellbar	Ja	
Schweisssdüse / Nahtbreite	40 mm	1.57 in
LQS	Nein	
Bürstenloser Gebläsemotor	Nein	
Länge	500 mm	19.68 in
Breite	310 mm	12.2 in
Höhe	300 mm	11.81 in
Gewicht	15 kg	33.06 lb
Stecker	CEE blau, 3-polig, 16A; CN, 3-polig, 16A; EU, 3-polig, 16A; US, 3-polig, 15A; ohne Stecker	
Netzkabellänge	3 m	9.84 ft
Zulassungen	CB Zertifizierung; CE	
Schutzklasse	I	
Ursprungsland	Schweiz	



UNIPLAN 310

Lieferumfang

Gerätekoffer

Produktartikel

177.401	UNIPLAN 310, 230V/3450W, 40mm, CN 16(2P+PE)
177.402	UNIPLAN 310, 230V/3450W, 30mm, CN 16(2P+PE)
179.074	UNIPLAN 310, 120V/1800W, 30mm, US-Stecker
179.075	UNIPLAN 310, 120V/1800W, 40mm, US-Stecker
179.080	UNIPLAN 310, 230V/3450W, 20mm, CEE 3/16
179.081	UNIPLAN 310, 230V/3450W, 30mm, CEE 3/16
179.082	UNIPLAN 310, 230V/3450W, 40mm, CEE 3/16
179.083	UNIPLAN 310, 230V/3450W, 40mm, EU-Stecker
179.084	UNIPLAN 310, 230V/3450W, 30mm, EU-Stecker
179.085	UNIPLAN 310, 230V/3450W, 20mm, EU-Stecker
179.089	UNIPLAN 310, 230V/3450W, 40mm, ohne Stecker