

WELDPLAST S1



Over het product



Technische gegevens

Artikel	148.394; 148.395; 148.396; 156.140; 169.928; 177.272	
Spanning	100 V; 120 V; 220 V; 230 V	
Frequentie	50/60 Hz; 60 Hz	
Vermogen	1500-1800 W	
Lasdraad	ø 3-4 mm / 0.12-0.16 in	
Materiaaluitgang ø 3 mm	0.2-0.5 kg/h	0.44-1.1 lb/h
Materiaaluitgang ø 4 mm	0.3-0.8 kg/h	0.66-1.76 lb/h
Lasmaterialen	ABS; ECTFE; FPO; HDPE; LDPE; LLDPE; PA; PC; PP; PVC-C; PVC-U; PVDF; TPO	
Lasbare plaat/membraandikte	5-12 mm	0.19-0.47 in
Luchtgids	Extern	
Schroefverwarming	Spoelverwarmer	
Luchttemperatuurregeling	Gesloten lus	
LQS	Geen	
Weergave	Ja	
Borstelloze blaasmotor	Ja	
Borstelloze aandrijfmotor	Geen	
LED-werklamp	Ja	
Lengte	435 mm	17.12 in
Breedte	91 mm	3.58 in
Hoogte	264 mm	10.39 in
Gewicht	4.7 kg	10.36 lb



WELDPLAST S1

Technische gegevens

Lengte voedingskabel	3-5 m	9.84-16.4 ft
Stekker	CEE blauw, 3-polig, 16A; EU, 3-polig, 16A; KR, 3-polig, 16A; UK, 3-polig, 13A; zonder stekker	
Geluidsemissieniveau	76 dB (A)	
Goedkeuringen	CB Certificering; CE; KC	
Beschermingsklasse	I	
Land van herkomst	Zwitserland	

Omvang van de levering

Gereedschapskoffer

Artikel

148.394	WELDPLAST S1, 100V/1500W, zonder stekker
148.395	WELDPLAST S1, 120V/1800W, zonder stekker
148.396	WELDPLAST S1, 230V/1600W, EU stekker
156.140	WELDPLAST S1, 230V/1600W, VK stekker
169.928	WELDPLAST S1, 220V/1500W, KR stekker
177.272	WELDPLAST S1, 230V/1600W, CEE 3/16