

UNIROOF 700



关于产品



技术数据

订货号	165.834; 165.835; 165.836; 165.837; 169.235; 169.236; 169.237; 170.210; 176.840	
电压	100 V; 120 V; 230 V	
频率	50/60 Hz	
功率	1500–3680 W	
速度	1–10 m/min	3.28–32.81 ft/min
温度	100–620 °C	212–1148 °F
风量可调	有	
风嘴/焊缝宽度	40–80 mm	1.57–3.14 in
焊接材料	ECB; EPDM; EVA; FPO; PIB; PVC; TPE; TPO; TPU; 沥青	
焊接质量监控 (LQS)	有	
无刷鼓风机电机	有	
长度	475 mm	18.7 in
宽度	244–360 mm	9.6–14.17 in
高度	260 mm	10.23 in
重量	17–19.9 kg	37.47–43.87 lb
插头	CEE蓝色, 3极, 16A.; CH T23, 3极, 16A; JP, 3极, 15A; KR, 3极, 16A; 无插头; 欧盟, 3极, 16A; 美国, 2极, 15A, 极化处理; 英国, 3极, 13A	
电源线长度	3 m	9.84 ft
认证	CB认证; CE	



UNIROOF 700

技术数据

保护等级	I
RAL	有
原籍国	瑞士

交付范围

金属垫片; 钢丝刷; 内六角扳手 4 mm; 工具箱

订货号

165.834	UNIROOF 700, 230V/3680W, 40mm, 欧标插头
165.835	UNIROOF 700, 120V/1800W, 40mm, 美标插头
165.836	UNIROOF 700, 230V/3680W, 40mm, 无插头
165.837	UNIROOF 700, 100V/1500W, 40mm, 日标插头
169.235	UNIROOF 700, 230V/3680W, 40mm, CEE 3/16
169.236	UNIROOF 700, 230V/3680W, 40mm, 韩标插头
169.237	UNIROOF 700, 120V/1800W, 40mm, CEE 3/16
170.210	UNIROOF 700, 230V/3680W, 80mm, 欧标插头
176.840	UNIROOF 700, 230V/3680W, 40mm, 欧标插头