

UNIROOF 700



To the product

Technical data

| | | |
|-----------------------------|---|-------------------|
| Article | 165.834; 165.835; 165.836; 165.837; 169.235; 169.236; 169.237; 170.210; 176.840 | |
| Voltage | 100 V; 120 V; 230 V | |
| Frequency | 50/60 Hz | |
| Power | 1500-3680 W | |
| Speed | 1-10 m/min | 3.28-32.81 ft/min |
| Temperature | 100-620 °C | 212-1148 °F |
| Air volume adjustable | Yes | |
| Welding nozzle / seam width | 40-80 mm | 1.57-3.14 in |
| Welding materials | Bitumen; ECB; EPDM; EVA; FPO; PIB; PVC; TPE; TPO; TPU | |
| LQS | Yes | |
| Brushless blower motor | Yes | |
| Length | 475 mm | 18.7 in |
| Width | 244-360 mm | 9.6-14.17 in |
| Height | 260 mm | 10.23 in |
| Weight | 17-19.9 kg | 37.47-43.87 lb |
| Plug | CEE blue, 3 poles, 16A; CH T23, 3 poles, 16A; EU, 3 poles, 16A; JP, 3 poles, 15A; KR, 3 poles, 16A; UK, 3 poles, 13A; US, 2 poles, 15A, polarized; without plug | |
| Power cable length | 3 m | 9.84 ft |
| Approvals | CB Certification; CE | |



UNIROOF 700

Technical data

| | |
|-------------------|-------------|
| Protection class | I |
| RAL | Yes |
| Country of origin | Switzerland |

Scope of delivery

Welding plate; Wire brush, stainless steel; Allen wrench 4 mm; Tool case

Product items

| | |
|---------|---|
| 165.834 | UNIROOF 700, 230V/3680W, 40mm, EU plug |
| 165.835 | UNIROOF 700, 120V/1800W, 40mm, US plug |
| 165.836 | UNIROOF 700, 230V/3680W, 40mm, w/o plug |
| 165.837 | UNIROOF 700, 100V/1500W, 40mm, JP plug |
| 169.235 | UNIROOF 700, 230V/3680W, 40mm, CEE 3/16 |
| 169.236 | UNIROOF 700, 230V/3680W, 40mm, KR plug |
| 169.237 | UNIROOF 700, 120V/1800W, 40mm, CEE 3/16 |
| 170.210 | UNIROOF 700, 230V/3680W, 80mm, EU plug |
| 176.840 | UNIROOF 700, 230V/3680W, 40mm, CH plug |