

HOT JET A



To the product

Technical data

Article	144.590; 144.591; 144.592; 144.593; 144.594; 144.595; 144.603; 144.604; 144.605; 144.607; 144.608; 144.609	
Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	600-1050 W	
Temperature	60-550 °C	140-1022 °F
Temperature setting stepless	Yes	
Airflow (20°C)	40-150 l/min	1.41-5.29 cfm
Stepless air volume adjustment	Yes	
Static pressure	2000-2200 Pa	0.29-0.31 psi
Eco-Mode	Yes	
Display	Yes	
e-Drive	Yes	
Outdoor use	Yes	
Nozzle connection ø	21.3 mm / 0.85 in; 31.5 mm / 1.25 in	
Length	277 mm	10.9 in
Device diameter	68 mm	2.67-3.22 in
Handle diameter	45 mm	1.77-1.92 in
Weight	0.59 kg	1.3 lb
Power cable length	3 m	9.84 ft



HOT JET A

Technical data

Plug	AU, 3 poles, 10A; CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; JP, 2 poles, 15A; US, 2 poles, 15A, polarized
Approvals	CE
Protection class	II
Country of origin	Switzerland

Product items

144.590	HOT JET 500 A, 230V/1050W, EU plug
144.591	HOT JET 500 A, 230V/1050W, CH plug
144.592	HOT JET 500 A, 230V/1050W, AU plug
144.593	HOT JET 500 A, 230V/1050W, CN plug
144.594	HOT JET 500 A, 120V/1050W, US plug
144.595	HOT JET 500 A, 100V/1050W, JP plug
144.603	HOT JET 302 A, 230V/600W, EU plug
144.604	HOT JET 302 A, 230V/600W, CH plug
144.605	HOT JET 302 A, 230V/600W, AU plug
144.607	HOT JET 302 A, 230V/600W, CN plug
144.608	HOT JET 302 A, 120V/600W, US plug
144.609	HOT JET 302 A, 100V/500W, JP plug