

VARIMAT 710



To the product



Technical data

Article	179.780; 179.781; 179.782	
Voltage	230 V; 400 V	
Frequency	50/60 Hz	
Power	3680-5700 W	
Speed	1-12 m/min	3.28-39.37 ft/min
Temperature	100-620 °C	212-1148 °F
Air volume adjustable	Yes	
Welding nozzle / seam width	40 mm	1.57 inch
Welding materials	ECB; EPDM; EVA; FPO; PIB; PO; PVC; PVC-P; TPE; TPO; TPU	
LQS	Yes	
Brushless blower motor	Yes	
Length	605 mm	23.81 inch
Width	335 mm	13.18 inch
Height	373 mm	14.68 inch
Weight	37.5 kg	82.67 lb
Plug	CEE red, 5 poles, 16A; without plug	
Power cable length	5 m	16.4 ft
Approvals	CB Certification; CE	
Protection class	I	
RAL	Yes	
Country of origin	Switzerland	



VARIMAT 710

Scope of delivery

Welding plate; Wire brush, stainless steel; Nozzle adjustment gauge VARIMAT 700/500/300; Screwdriver, Torx T20; Allen wrench 4 mm; Rolling Transport Case VARIMAT 700/500/300

Product items

179.780	VARIMAT 710, 230V/3680W, 40mm, w/o cable
179.781	VARIMAT 710, 400V/5700W, 40mm, CEE 5/16
179.782	VARIMAT 710, 230V/3680W, 40mm, °F, w/o plug