HOT JET 302 A



To the product

Technical data

Article	144.603; 144.604; 144.605; 144.607; 144.608; 144.609	
Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	500–600 W	
Temperature	60–550 °C	140–1022 °F
Temperature setting stepless	Yes	
Airflow (20°C)	40–95 l/min	1.41–3.35 cfm
Stepless air volume adjustment	Yes	
Static pressure	2000 Pa	0.29 psi
Eco-Mode	Yes	
Display	Yes	
e-Drive	Yes	
Outdoor use	Yes	
Nozzle connection ø	21.3 mm / 0.85 in	
Length	277 mm	10.9 inch
Device diameter	68 mm	2.67 inch
Handle diameter	45 mm	1.77 inch
Weight	0.53 kg	1.16 lb
Power cable length	3 m	9.84 ft
Plug	AU, 3 poles, 10A; CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; JP, 2 poles, 15A; US, 2 poles, 15A, polarized	

© Copyright Leister Technologies AG, 2026 | Subject to changes

HOT JET 302 A

Technical data

Approvals	CE
Protection class	II
Country of origin	Switzerland

Product items

144.603	HOT JET 302 A, 230V/600W, EU plug
144.604	HOT JET 302 A, 230V/600W, CH plug
144.605	HOT JET 302 A, 230V/600W, AU plug
144.607	HOT JET 302 A, 230V/600W, CN plug
144.608	HOT JET 302 A, 120V/600W, US plug
144.609	HOT JET 302 A, 100V/500W, JP plug

© Copyright Leister Technologies AG, 2026 | Subject to changes