TRIAC ST

TRIAC ST, 120V/1600W, CEE 3/16
Article 141.308

To the product item

Technical data

Article	141.308	
Voltage	120 V	
Frequency	50/60 Hz	
Power	1600 W	
Temperature	40–700 °C	104–1292 °F
Temperature setting stepless	Yes	
Airflow (20°C)	240 l/min	8.47 cfm
Stepless air volume adjustment	No	
Static pressure	3000 Pa	0.43 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in	
Length	338 mm	13.3 in
Device diameter	90 mm	3.54 in
Handle diameter	56 mm	2.2 in
Weight	0.99 kg	2.18 lb
Power cable length	3 m	9.84 ft
Plug	CEE yellow, 3 poles, 16A	
Noise emission level	67 dB (A)	
Approvals	CE	
Protection class	II	
Country of origin	Switzerland	

© Copyright Leister Technologies AG, 2025 | Subject to changes

TRIAC ST

TRIAC ST, 120V/1600W, CEE 3/16
Article 141.308

Scope of delivery

116.586 Tool case

© Copyright Leister Technologies AG, 2025 | Subject to changes